



PMMA-Based Universal Primer

HIGH PERFORMANCE MULTI-SURFACE PRIMER

A solvent-free, 2-component methacrylate resin primer that provides excellent adhesion onto absorbent and non-absorbent substrates.

This Primer is used in conjunction with the PMMA range of systems. It delivers high performance adhesion to substrates such as concrete, cement screed, untreated steel, stainless steel and more.

- Hard dry in just 35 - 45 minutes* (see Data Sheet)
- A suitable multi-surface primer as part of PMMA-Based Waterproofing Coating, Self-Levelling Mortar, Top Coat / Sealer Coat and Anti-Slip Paint systems.
- Provides excellent adhesion onto absorbent and non-absorbent substrates
- Solvent-free
- Packaged in 10kg container



+44 (0) 1698 591 635

info@cactusindustrial.com

www.cactusindustrial.com



PMMA-Based Universal Primer

PMMA-BASED UNIVERSAL PRIMER APPLICATION AREAS INCLUDE, BUT ARE NOT LIMITED TO:

- Flat and Pitched Roof Areas
- Offshore Decks, Lay Down Areas and Walkways
- Balcony Waterproofing
- Production Areas
- Car Parking
- Warehouses
- HVAC and Ducting

Product Data

Product Description	A solvent-free, 2-component methacrylate resin system multi-surface primer
Volume Solids	100%
Typical Thickness	40 microns DFT minimum
Theoretical Coverage	3.3m ² /per kg

Substrate Temperature	PMMA Catalyst % pbw.	Pot Life approx. min.	Hardening Time approx. min.
0°C	3.0	32 - 36	50 - 60
+10°C	2.0	18 - 22	45 - 55
+20°C	1.5	12 - 14	35 - 45

For substrate temperatures of -10°C, please refer to PMMA Additive LT Technical Data Sheet.

